

# Applications of 3M™ Marine Preferred Masking Tapes

Use this chart to select the right masking tape for the right application

Product Ref.	3060	218	471	225	256	2090
<b>Application</b>						
<b>Critical Paint Masking</b> (above waterline hull and top side/deck painting)						
<b>Bottom Painting</b>						
<b>Paint Striping/ Color Separation</b> (boot, cove, shear or waterline stripe painting)						
<b>Brightwork Finishing and Coating</b> (varnish, stain and sealing)						
<b>Outdoor Masking</b> (bundling and protecting over 24 hours)						
			Up to 1 Mo.	Up to 1 Mo.	Up to 5 Days	Up to 7 Days

\*\* Not recommended for use with lacquers or on lacquered surfaces.



# Paint Striping Tapes


## Problems

## Solutions


### Using 3M Products



To allow easy, one-piece removability use :




3M 2211 for general masking




3M 2090 for critical paint masking



To mask parts requiring conformability use :




3M 218 for curved areas masking




3M 471 for detailed stripe painting



To provide sharp paint edge use :




3M 2090 for bottom painting



3M 256 for straight paint lines




To avoid adhesive transfer after a few days use :



3M 2090 for clean removal up to 7 days



To hold power without lifting use :



3M 471 for masking up to 30 days